
Worksheet: Computation Graphs for Async-Finish and Future Constructs

- 1) Can you write pseudocode with <u>async & finish</u> constructs that generates a Computation Graph with the same ordering constraints as the graph on the right? If so, provide a sketch of the program. If not, why not?
- 2) Can you write pseudocode with <u>future & get</u> constructs that generates a Computation Graph with the same ordering constraints as the graph on the right? If so, provide a sketch of the program. If not, why not?






Worksheet solution

1) Can you write pseudocode with <u>async-finish</u> constructs that generates a Computation Graph with the same ordering constraints as the graph on the right? If so, provide a sketch of the program.

No. Finish cannot be used to ensure that D only waits for B and C, while E waits only for C.

2) Can you write pseudocode with <u>future async-get</u> constructs that generates a Computation Graph with the same ordering constraints as the graph on the right? If so, provide a sketch of the program.

Yes, see program sketch with dummy return values.





Worksheet solution (contd.)

```
var A = future(() -> {
       return "A"; });
2.
    var B = future(() -> {
       A.get(); return "B"; });
    var C = future(() -> {
       A.get(); return "C"; });
6.
    var D = future(() -> {
       // Order of B.get() & C.get() doesn't matter
8.
       B.get(); C.get(); return "D"; });
10. var E = future(() \rightarrow \{
       C.get(); return "E"; });
11.
12. var F = future(() \rightarrow \{
       D.get(); E.get(); return "F"; });
14. F.get();
```

