

Lab 7: Java Threads and Locks

Instructor: Mack Joyner

Course Wiki: <http://comp322.rice.edu>

Staff Email: comp322-staff@mailman.rice.edu

Goals for today's lab

- Experimentation with Java threads
- Experimentation with regular locks and read-write locks in Java

This lab can be downloaded from the following GitHub repository <https://classroom.github.com/a/o7vvKlzM>. Use the git command-line client or IntelliJ to checkout the project into appropriate directories locally.

In today's lab, you need to use NOTS to run performance tests. If you need any guidance on how to submit jobs on NOTS manually, please refer to earlier labs or ask a member of the teaching staff.

1 Conversion to Java threads: Spanning Tree

1. The `SpanningTreeSeq.java` program is an example sequential solution to the spanning tree problem. The `SpanningTreeAtomicHjLib.java` program is a provided parallel solution to the minimum spanning tree problem. This version uses `finish` and `async` constructs along with an `AtomicReference`.
2. Your task is to convert `SpanningTreeAtomicHjLib.java` to a Java program that uses threads instead of `HJlib` tasks. You should modify the provided `SpanningTreeAtomicThreads.java` file, and use Java thread methods instead of `finish/async`. (The `AtomicReference` calls can stay unchanged.) There are `TODOs` in the file to guide you.
3. You have been provided with tests for your parallel spanning tree implementation in `SpanningTreePerformanceTest`. To complete this portion of the lab, you should submit these performance tests to NOTS by modifying the provided `myjob.slurm` template and submitting manually.

2 Programming Tips and Pitfalls for Java Threads

- Remember to call the `start()` method on any thread that you create. Otherwise, the thread's computation does not get executed.
- Since the `join()` method may potentially throw an `InterruptedException`, you will either need to enclose each call to `join()` within a *try-catch block*, or add a *throws InterruptedException* clause to the definition of the method that includes the call to `join()`.

3 Sorted Linked List Example using Java's Synchronized Methods

In today's lab you will practice using Java Locks. Java Locks were introduced in Lecture 26. **Note that the sorted list exercises will not have a dependency on `HJlib`; you will not need the `-javaagent` command line option in the run configurations you use in IntelliJ for these exercises.**

In the provided code there are three files to focus on: `SyncList.java`, `CoarseList.java`, and `RWCoarseList.java`.

`SyncList.java` implements a thread-safe sorted linked list that supports `contains()`, `add()` and `remove()` methods. The provided `testSynchronized` test in `SortedListPerformanceTest.java` repeatedly calls these three methods with a distribution that aims for 99% read operations (calls to `contains()`) and 1% add operations. Since all three methods are declared as `synchronized` in `SyncList.java`, all calls will be serialized on a single `SyncList` object.

For this section, simply verify that you can compile and run the `testSynchronized` test locally using either IntelliJ or Maven. This test (and the others for the following sections of this lab) tests the throughput in operations per second of each concurrent list implementation with varying numbers of threads. The most important metric printed is the “Operations per second”.

4 Use of Coarse-Grained Locking instead of Java’s Synchronized Methods

The goal of this section is to replace the use of Java’s synchronized method in `SyncList.java` by using explicit locking instead. For this section, your tasks are as follows:

1. Modify `CoarseList.java` to allocate a single instance of a `ReentrantLock` when creating an instance of `CoarseList`. The term *coarse locking* is used for cases like this when a single lock is used to protect the entire data structure, as opposed to *fine-grained locking* in which different locks may be used to protect different components (e.g., nodes) in a data structure.
2. Replace the three occurrences of “synchronized” in `SyncList` by appropriate calls to `lock()` and `unlock()` on the allocated `ReentrantLock`. Remember to use a try-finally block as follows to ensure that `unlock()` is always called:

```
lock.lock();  
try { ... }  
finally { lock.unlock(); }
```

3. Compile and run the `testCoarseGrainedLocking` test in `SortedListPerformanceTest.java`. Compare its performance to testing the provided synchronized version using `testSynchronized`.

5 Use of Read-Write Locks

The goal of this section is to replace the use of a `ReentrantLock` in `CoarseList.java` by a `ReentrantReadWriteLock`, so as to leverage the fact that the majority of the operations (99% by default) are calls to `contains()` which are read-only in nature and can execute in parallel with each other. For this section, your tasks are as follows:

1. Replace the instance of `ReentrantLock` in `CoarseList.java` by an instance of `ReentrantReadWriteLock`.
2. Replace the calls to `lock()` by `readLock.lock()` or `writeLock.lock()` where appropriate in `RWCoarseList.java`. Likewise for `unlock()`.
3. Compile and run the `testReadWriteLocks` test in `SortedListPerformanceTest.java`. Compare its performance to the locking and synchronized versions using `testSynchronized` and `testCoarseGrainedLocking`.

6 Testing on NOTS

Now that we have implementations of a concurrent list using synchronized, locks, and read-write locks we will test their performance on the NOTS cluster to measure the actual performance of each implementation without interference on your laptop.

To do so, you should use the provided `myjob.slurm` file. As usual, when using the `myjob.slurm` file please open it to fix any TODO items.

7 Turning in your lab work

For lab 7, you will need to turn in your work by Tuesday, April 13, 2021 at 12 pm (noon), as follows.

1. Show your work to an instructor or TA to get credit for this lab. In particular, the TAs will want to see the output of `testSynchronized`, `testCoarseGrainedLocking`, and `testReadWriteLocks`, and `testSpanningTreeThreads` running on NOTS through the provided SLURM script.
2. Commit your work to your lab7 folder. Check that all the work for today's lab is in your lab7 directory by opening <https://classroom.github.com/a/o7vvKIzM> in your web browser and checking that your changes have appeared.