
COMP 322: Fundamentals of Parallel Programming

Lecture 6: Memoization

Instructors: Vivek Sarkar, Mack Joyner
Department of Computer Science, Rice University
{vsarkar, mjoyner}@rice.edu

<http://comp322.rice.edu>

COMP 322

Lecture 6

23 January 2017




Worksheet #5: Computation Graphs for Async-Finish and Future Constructs

1) Can you write pseudocode with async-finish constructs that generates a Computation Graph with the same ordering constraints as the graph on the right? If so, provide a sketch of the program.

No. Finish cannot be used to ensure that D waits for both B and C, while E waits only for C.


2) Can you write pseudocode with future async-get constructs that generates a Computation Graph with the same ordering constraints as the graph on the right? If so, provide a sketch of the program.

Yes, see program sketch with void futures. A dummy return value can also be used.



Worksheet #5 solution (contd)

```
1. HjFuture<String> A = future((()) -> {  
2.     return "A"; });  
3. HjFuture<String> B = future((()) -> {  
4.     A.get(); return "B"; });  
5. HjFuture<String> C = future((()) -> {  
6.     A.get(); return "C"; });  
7. HjFuture<String> D = future((()) -> {  
8.     // Order of B.get() & C.get() doesn't matter  
9.     B.get(); C.get(); return "D"; });  
10. HjFuture<String> E = future((()) -> {  
11.     C.get(); return "E"; });  
12. HjFuture<String> F = future((()) -> {  
13.     D.get(); E.get(); return "F"; });  
14. F.get();
```



3

COMP 322, Spring 2017 (V. Sarkar, M. Joyner)



Background: Functional Programming

- Eliminate side-effects
 - emphasizes functions whose results that depend only on their inputs and not on any other program state
 - calling a function, $f(x)$, twice with the same value for the argument x will produce the same result both times

Helpful Link: http://en.wikipedia.org/wiki/Functional_programming

4

COMP 322, Spring 2017 (V. Sarkar, M. Joyner)



Example: Binomial Coefficient

- The coefficient of the x^k term in the polynomial expansion of the binomial power $(1 + x)^n$
- Number of sets of k items that can be chosen from n items
- Indexed by n and k
 - written as $C(n, k)$
 - read as “ n choose k ”
- Factorial Formula: $C(n, k) = \frac{n!}{k!(n-k)!}$
- Recursive Formula
$$C(n, k) = C(n - 1, k - 1) + C(n - 1, k)$$
Base cases: $C(n, n) = C(n, 0) = C(0, k) = 1$

Helpful Link: http://en.wikipedia.org/wiki/Binomial_coefficient



Example: Binomial Coefficient (Recursive Sequential version)

```
1. int choose(int N, int K {  
2.     if (N == 0 || K == 0 || N == K) {  
3.         return 1;  
4.     }  
5.     int left = choose (N-1, K - 1);  
6.     int right = choose (N-1, K);  
7.     return left + right;  
8. }
```



Example: Binomial Coefficient (Parallel Recursive Pseudocode)

```
1. Integer choose(int N, int K) {  
2.     if (N == 0 || K == 0 || N == K) {  
3.         return 1;  
4.     }  
5.     future<Integer> left =  
6.         future { return choose (N-1, K-1); }  
7.     future<Integer> right =  
8.         future { return choose (N-1, K); }  
9.     return left.get() + right.get();  
10. }
```


- Use of futures supports incremental parallelization with low developer effort

7

COMP 322, Spring 2017 (V. Sarkar, M. Joyner)



What inefficiencies do you see in the recursive Binomial Coefficient algorithm?



8

COMP 322, Spring 2017 (V. Sarkar, M. Joyner)



Memoization


- Memoization - saving and reusing previously computed values of a function rather than recomputing them
 - A optimization technique with space-time tradeoff
- A function can only be memoized if it is *referentially transparent*, i.e. functional
- Related to caching
 - memoized function "remembers" the results corresponding to some set of specific inputs
 - memoized function populates its cache of results transparently on the fly, as needed, rather than in advance

Helpful Link: <http://en.wikipedia.org/wiki/Memoization>



Pascal's Triangle is an example of Memoization

$$C(n, k) = C(n - 1, k - 1) + C(n - 1, k)$$



Example: Binomial Coefficient (sequential memoized version)

```
1. final Map<Pair<Int, Int>, Int> cache = new ...;

2. int choose(int N, int K) {
3.     Pair<Int, Int> key = Pair.factory(N, K);
4.     if (cache.contains(key)) {
5.         return cache.get(key);
6.     }
7.     if (N == 0 || K == 0 || N == K) {
8.         return 1;
9.     }
10.    int left = choose (N - 1, K - 1);
11.    int right = choose (N - 1, K);
12.    int result = left + right;
13.    cache.put(key, result);
14.    return result;
15. }
```

11

COMP 322, Spring 2017 (V. Sarkar, M. Joyner)



Example: Binomial Coefficient (parallel memoized version w/ futures)

```
1. final Map<Pair<Int, Int>, future<Integer>> cache = new ...;

2. Integer choose(final int N, final int K) {
3.     final Pair<Int, Int> key = Pair.factory(N, K);
4.     if (cache.contains(key)) {
5.         return cache.get(key).get();
6.     }
7.     future<Integer> f = future {
8.         if (N == 0 || K == 0 || N == K) return 1;
9.         future<Integer> left = future { return choose (N-1, K-1); }
10.        future<Integer> right = future { return choose (N-1, K); }
11.        return left.get() + right.get();
12.    }
13.    cache.put(key, f);
14.    return f.get();
15. }
```

- Assumes availability of a “thread-safe” cache library, e.g., ConcurrentHashMap

12

COMP 322, Spring 2017 (V. Sarkar, M. Joyner)



Announcements & Reminders

- **IMPORTANT:**
 - Watch video & read handout for topic 2.3 for next lecture on Wednesday, Jan 25th
- HW1 was posted on the course web site (<http://comp322.rice.edu>) on Jan 11th, and is due on Jan 25th
- Quiz for Unit 1 (topics 1.1 - 1.5) is due by Jan 27th on Canvas
- See course web site for all work assignments and due dates
- Use Piazza (public or private posts, as appropriate) for all communications re. COMP 322
- See Office Hours link on course web site for latest office hours schedule. Group office hours are now scheduled during 3pm - 4pm on MWF in DH 3092 (default room but alternate room may need to be used on some days — an announcement will be made in the lecture on those days)

