

COMP 322: Fundamentals of Parallel Programming

Lecture 25: Java Threads, Java synchronized statement

Mack Joyner
mjoyner@rice.edu

<http://comp322.rice.edu>



One possible solution to Worksheet #24

1) Write a sketch of the pseudocode for a Java threads program that exhibits a data race using `start()` and `join()` operations.

```
1. // Start of thread t0 (main program)
2. sum1 = 0; sum2 = 0; // Assume that sum1 & sum2 are fields
3. // Compute sum1 (lower half) and sum2 (upper half) in parallel
4. final int len = X.length;
5. Thread t1 = new Thread(() -> {
6.     for(int i=0 ; i < len/2 ; i++) sum1+=X[i];});
7. t1.start();
8. Thread t2 = new Thread(() -> {
9.     for(int i=len/2 ; i < len ; i++) sum2+=X[i];});
10. t2.start();
11. int sum = sum1 + sum2; //data race between t0 & t1, and t0 & t2
12. t1.join(); t2.join();
```



One possible solution to Worksheet #24 (contd)

2) Write a sketch of the pseudocode for a Java threads program that exhibits a data race using synchronized statements.

```
1. // Start of thread t0 (main program)
2. sum = 0; // static int field
3. Object a = new ... ;
4. Object b = new ... ;
5. Thread t1 = new Thread(() ->
6.     { synchronized(a) { sum++; } });
7. Thread t2 = new Thread(() ->
8.     { synchronized(b) { sum++; } });
9. t1.start();
10. t2.start(); // data race between t1 & t2
11. t1.join(); t2.join();
```



Unit 7.1: Java Threads (Recap)

- Execution of a Java program begins with an instance of Thread created by the Java Virtual Machine (JVM) that executes the program's main() method.
- Parallelism can be introduced by creating additional instances of class Thread that execute as parallel threads.

```
1 public class Thread extends Object implements Runnable {
2     Thread() { ... } // Creates a new Thread
3     Thread(Runnable r) { ... } // Creates a new Thread with Runnable object r
4     void run() { ... } // Code to be executed by the thread
5     // Case 1: If this thread was created with a Runnable object,
6     //           then that object's run method is called.
7     // Case 2: If this class is subclassed, the run method
8     //           in the subclass is called.
9     void start() { ... } // Causes this thread to start
10    void join() { ... } // Wait for this thread to die
11    void join(long m) // Wait at most m milliseconds for thread to die
12    static Thread currentThread() // Returns currently executing thread
13    . . .
14 }
```

A lambda can be passed as a Runnable

Listing 3: java.lang.Thread class




Unit 7.2: Objects and Locks in Java --- synchronized statements and methods (Recap)

- Every Java object has an associated *lock* acquired via:
 - `synchronized` statements
 - `synchronized(foo) { // acquire foo's lock
// execute code while holding foo's lock
} // release foo's lock`
 - `synchronized` methods
 - `public synchronized void op1() { // acquire 'this' lock
// execute method while holding 'this' lock
} // release 'this' lock`
- Java language does not enforce any relationship between object used for locking and objects accessed in isolated code
 - If same object is used for locking and data access, then the object behaves like a monitor
- Locking and unlocking are **automatic**
 - Locks are released when a `synchronized` block exits
 - By normal means: end of block reached, `return`, `break`
 - When an exception is thrown and not caught



Implementation of Java synchronized statements/methods

- Every object has an associated lock
- “synchronized” is translated to matching `monitorenter` and `monitorexit` bytecode instructions for the Java virtual machine
 - `monitorenter` requests “ownership” of the object’s lock
 - `monitorexit` releases “ownership” of the object’s lock
- If a thread performing `monitorenter` does not gain ownership of the lock (because another thread already owns it), it is placed in an unordered “entry set” for the object’s lock



Monitors – a Diagrammatic summary




Figure 20-1. A Java monitor.

Figure source: <http://www.artima.com/insidejvm/ed2/images/fig20-1.gif>



What if you want to wait for shared state to satisfy a desired property? (Bounded Buffer Example)

```
1. public synchronized void insert(Object item) { // producer
2.     // TODO: wait till count < BUFFER SIZE
3.     ++count;
4.     buffer[in] = item;
5.     in = (in + 1) % BUFFER SIZE;
6.     // TODO: notify consumers that an insert has been performed
7. }

9. public synchronized Object remove() { // consumer
10.    Object item;
11.    // TODO: wait till count > 0
12.    --count;
13.    item = buffer[out];
14.    out = (out + 1) % BUFFER SIZE;
15.    // TODO: notify producers that a remove() has been performed
16.    return item;
17. }
```




The Java wait() Method

- A thread can perform a `wait()` method on an object that it owns:
 1. the thread releases the object lock
 2. thread state is set to blocked
 3. thread is placed in the wait set
- Causes thread to wait until another thread invokes the `notify()` method or the `notifyAll()` method for this object.
- Since interrupts and spurious wake-ups are possible, this method should always be used in a loop e.g.,

```
synchronized (obj) {  
    while (<condition does not hold>)  
        obj.wait();  
    ... // Perform action appropriate to condition  
}
```
- Java's wait-notify is related to "condition variables" in POSIX threads



Entry and Wait Sets



The notify() Method

When a thread calls `notify()`, the following occurs:

1. selects an arbitrary thread T from the wait set
2. moves T to the entry set
3. sets T to Runnable

T can now compete for the object's lock again



Multiple Notifications

- `notify()` selects an arbitrary thread from the wait set.
 - This may not be the thread that you want to be selected.
 - Java does not allow you to specify the thread to be selected
- `notifyAll()` removes ALL threads from the wait set and places them in the entry set. This allows the threads to decide among themselves who should proceed next.
- `notifyAll()` is a conservative strategy that works best when multiple threads may be in the wait set



insert() with wait/notify Methods

```
public synchronized void insert(Object item) {  
    while (count == BUFFER SIZE) {  
        try {  
            wait();  
        }  
        catch (InterruptedException e) { }  
    }  
    ++count;  
    buffer[in] = item;  
    in = (in + 1) % BUFFER SIZE;  
    notify();  
}
```



remove() with wait/notify Methods

```
public synchronized Object remove() {  
    Object item;  
    while (count == 0) {  
        try {  
            wait();  
        }  
        catch (InterruptedException e) { }  
    }  
    --count;  
    item = buffer[out];  
    out = (out + 1) % BUFFER SIZE;  
    notify();  
    return item;  
}
```



Complete Bounded Buffer using Java Synchronization

```
public class BoundedBuffer implements Buffer
{
    private static final int BUFFER SIZE = 5;
    private int count, in, out;
    private Object[] buffer;
    public BoundedBuffer() { // buffer is initially empty
        count = 0;
        in = 0;
        out = 0;
        buffer = new Object[BUFFER SIZE];
    }
    public synchronized void insert(Object item) { // See previous slides
    }
    public synchronized Object remove() { // See previous slides
    }
}
```



Announcements

- Checkpoint 2 for Homework 3 is due **today** at 11:59pm
- The entire written + programming (Checkpoint #3) is due by Friday, April 3rd at 11:59pm
- Quiz for Unit 5 is due Monday, March 30th at 11:59pm
- Lab 5 is due Monday, March 30th at 11:59pm
 - Commit solution and slurm output file to svn to get checked off
- You now have 5 slip days (up from 3)



Worksheet #25: Bounded Buffer

Consider the case when multiple threads call `insert()` and `remove()` methods concurrently for a single `BoundedBuffer` instance with `SIZE >= 1`.

- 1) Can you provide an example in which the wait set includes a thread waiting at line 2 in `insert()` and a thread waiting at line 11 in `remove()`, in slide 8? If not, why not?
- 2) How would the code behave if all wait/notify calls (lines 2, 6, 11, 15) were removed from the `insert()` and `remove()` methods in slide 8?

